

## **MINIMUM SPECIFICATIONS FOR BOSS BULLET G**

Quantity of one (1) Boss model BULLET G portable air compressor (s) to include the following as standard equipment:

### ***COMPRESSOR:***

- Boss oil-flooded, rotary screw air-end designed to produce up to 70 CFM @ 100 PSIG continuously.
- Two-year warranty on the air-end.
- Vertical air/oil reservoir with filler port and sightglass. Bolt on lids and/or end plates not acceptable.
- Self-contained separator element with easy access spin-on housing.
- Aerodynamically designed cooling package with automatic thermal sensing control to ensure proper operating temperatures.
- Replaceable spin-on compressor lubricant filter with safety bypass and 25 micron rating.
- Dry-type air intake filter with replaceable element.
- Instrumentation to include: hourmeter and air pressure gauge, keyed off/on switch and choke.
- Safety devices to include: minimum pressure device, compressor lube hi-temp, automatic blowdown device, high-pressure relief valve, and necessary warning and information decals.
- Frame and canopy with easy access doors.
- 5 Gallon E.P.A / C.A.R.B. approved fuel tank.
- Dimensions not to exceed: 45”L x 20”W x 30”H
- Operation, parts, and maintenance manual.

***ENGINE:***

- Kohler CH-730 25 Hp, 4-cycle, v-twin, overhead valve, air-cooled gasoline engine.
- Two-year warranty on engine.
- Electronic ignition for broad RPM response.
- Cast-Iron cylinder liners for power and durability.
- 2013 E.P.A. & C.A.R.B. small engine certified.
- Overhead valve design for greater fuel efficiency and lower emissions.
- In line fuel filter.
- Oil fill in valve cover.
- Carburetor w/solenoid fuel shutdown for all weather consistent starting.
- Replacement dry element air cleaner with polyurethane wrapper.
- Rotating blower screen.
- Low oil pressure switch with safety shutdown.
- Muffler heat shield & guard.
- Oil cooler for heavy-duty power demands.
- Hydraulic valve lifter.
- 25 amp charging system.

***OPTIONAL:***

- Wheel mount with third wheel caster.
- Dual Pressure
- Remote stop/start/choke